

SOLVENT P

Solvent for dissolving methacrylate systems

FIELD OF APPLICATION

Solvent P is used to regulate the viscosity when applying methacrylate resin based products (Adingmarker P, Adingkolor RF, Adingkolor RB, Antikoroziin BR, Dekosil, Dekosil Plus). Also it is used for cleaning tools used for application of methacrylate and epoxy systems.

PROPERTIES

- lightly volatile liquid
- characteristic smell

TECHNICAL FEATURES

PROPERTY	METHOD	DECLARED VALUES
Appearance	-	colorless liquid
Density	-	0,85-0,9g/cm ³

METHOD OF APPLICATION

When it is used as solvent for methacrylate systems, dose it according to the declared values for each product and mix until it is homogenized completely. Using Solvent P optimize the viscosity of the products for application.

CONSUMPTION

depends of use

PACKAGING

metal packing: 0.9kg and 4kg.

STORAGE

In original sealed packaging, in dry rooms, at temperature of 5°C to 35°C. Keep the product away of heat and spark.

Shelf life: 12 months

Health hazards: Avoid contact of skin with product and inhalation of material. In case of accidental contact in the event of contamination of the skin, the same areas should be immediately washed with soap and water. If the material bursts into eyes, rinse immediately with water and seek medical attention. Wear protective gloves, clothing, eye and face protection. Additional information is provided in the Safety Data Sheet of the product.

Fire: Solvent P is flammable. Additional information is provided in the Safety Data Sheet of the product.

Cleaning and disposal: Old used packing should be disposed of in accordance with local regulations for appropriate type of waste.